

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 GOLD

PRODUCT CODE
ŠIFRA PROIZVODA

231701G



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD brušeno zlato
Uzidna baterija
Automatski prebacivač za tuš
Tuš ruža D.250mm - PTRUSPSG
Keramički mešač KEROX® 35mm - PKM35A
S.2 GOLD tuš crevo 150cm - PGC150SG
Tuš ručica - PTRECSG

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Brushed gold PVD finish
Build in the wall
Automatic shower diverter
Shower head D.250mm - PTRUSPSG
KEROX®35 mm ceramic cartridge - PKM35A
S.2 GOLD shower hose 150cm - PGC150SG
Hand shower - PTRECSG

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

